



AC630 Military-Grade Shockproof Portable Hard Drive

Special Rubber Structure for External Shocks

A single-piece rubber frame built from the internal structure to the exterior forms a cushion that can withstand direct impact forces, effectively reducing influences when accessing data during movement.



IP55 Certified for Dustproof and Waterproof Functions

AC630 ensures all-round protections against dust and spraying water, allowing users to enjoy their journey without worries.





*This product meets IP55 dustproof and waterproof requirements and offers protection in the normal environment. When not in use, please keep the USB cover tightly sealed. Gentle handling is recommended



Military-Grade Shockproof Protection

Compliant with MIL-STD-810G 516.6 Procedure IV (transit drop test), AC630 is resistant to falls of 1.22-meter height without losing data.





*Accidental drops in the normal environment will not cause damage to data, per U.S. MIL-STD-810G 516.6 procedure IV (transit drop test). Gentle handling is strongly recommended to ensure normal use.





Convenient Cable Carry Design

The thoughtful slot design keeps the cable neatly stowed when it is not in use.







- Military-grade MIL-STD-810G 516.6 (1.2M Drop Test) Compliance
- Cable Carry Design
- IP55 Dustproof and Water Resistant Protections
- Protective Rubber Structure for External Shocks

Ordering Information

Capacity	PN	EAN Code
1TB	AP1TBAC630T-1	4712389914941
2TB	AP2TBAC630T-1	4712389914958



Durable USB Type-A Female Connector

AC630 adopts USB Type-A female connector which is test-proven with a durability of 10,000 times plug and unplug cycles, providing safety guarantee for users.



Specification

- Color: Orange
- Capacity: 1TB / 2TB
- Interface: UHS Speed: SuperSpeed USB 3.2 Gen 1, backward compatible with USB 2.0 specification
- Weight: 250g (with cable)
- Dimensions: (L)143.3 x (W)92.9 x (H)20.1 mm
- Warranty: 3 Years





Apacer Technology Inc.

1F, No.32, Zhongcheng Rd., Tucheng Dist. New Taipei City 236, Taiwan R.O.C. Tel: +886-2-2267-8000

Fax: +886-2267-3410













