

Apacer

**Built for Speed.
Defined by Pattern.**

USB4 40Gbps



AS741 USB4 Gen3 x2 USB-C Portable SSD


This Apacer first USB4 AS741 portable SSD delivers up to 4000/3500 MB/s read/write speeds for users requiring fast data transfer and reliable mobile performance. Featuring USB-C plug-and-play connectivity and a durable silicone case with drop and scratch protection, it includes built-in cable storage and a lanyard hole for portability. Available in 1TB capacity, it also adopts eco-friendly silicone material for sustainable design.

Key Features


- Apacer first USB4 portable SSD
- Recognized as a 2026 Taiwan Excellence product
- USB-C interface and plug-and-play connection
- Silicone case with drop and scratch protection, built-in cable storage, and a lanyard hole for easy carry
- Read/write speed of up to 4000/3500 MB/s
- Passed 1.22m military-grade drop test
- Available in 1TB capacity
- Eco-friendly silicone case, sustainably designed



High Speed up to
4000 MB/s



Silicone Case
for Easy Carry



USB-C Connector



Passed Military-Grade
Drop Test



Selling Points

USB4 40 Gbps Performance. No Waiting.

AS741 is Apacer's first USB4 portable SSD, delivering speeds up to 40 Gbps (4000 MB/s) for fast, seamless transfers.



All-in-One Silicone Case for Easy Carry

The multifunctional silicone case combines protection, cable storage, and a lanyard hole—keeping everything secure and ready to go.

Plug & Play. Fast Across Devices

With USB4 Gen3 x2 interface, delivering read/write speeds of up to 4000/3500 MB/s. Its USB-C connection is compatible with a wide range of devices.



Durable Protection Against Drops and Scratches

AS741 is MIL-STD-810G certified and can withstand drops of up to 1.22 meters. Its protective silicone case helps prevent scratches, ensuring safer everyday portability.

- Model : AS741
- Color : Black
- Capacity : 1TB
- Material : Aluminum, Silicone
- Interface : USB4 and backward compatible with USB 3.2/USB 2.0
- NAND Flash : 3D NAND
- System Supported : Windows 11/10, macOS 10.8.X or above, Linux Kernel 2.6.X or above, Chrome OS
- Sequential Read/Write (MB/s) (Max)* : 4000/3500
- Standard Operating Temperature (°C) : 0°C ~ 55°C
- Accessory : USB-C to USB-C cable
- Dimensions (mm) : (L)72.00 x (W)72.00 x (H)16.00
- Weight : 64.3g
- Certificate : CE, UKCA, FCC, BSMI, VCCI
- Warranty : 3-year limited warranty

Ordering Information

FCC CE 紙 プリスター D33466 RoHS VCCI UKCA 10 再生 RoHS

